

ScanMaker 9800 XL

Specifications

Scan area	431.8 x 304.8 mm (A3)
Resolution	1600 x 3200 dpi, 12800 dpi interpolated
Colour depth	48 bit colour, 16 bit greyscale, 1 bit monochrome
Sensor	CCD with multisampling (off, 2x, 4x, 8x & 16x)
Optical density	3.7 Dmax
Light source	cold cathode tube
Interface	FireWire, SCSI II, USB 2.0
Detachable lid	yes
Power saver	yes
Weight	14.5 kg
Dimensions	628 x 376 x 130 mm



Options

Transparency unit	TMA 1600, scan area 406 x 305 mm
--------------------------	----------------------------------

Packaging

Cables	Mains cable, FireWire cable, USB cable
IT8 Target	Kodak Reflective (178 x 126 mm)
Documentation	ScanMaker 9800XL User Guide, Scanner Installation Guide, ScanWizard Pro User Guide, Packing List, ScanWizard Pro Quick Ref Guide, FireWire Card Quick Install Guide, Warranty & Registration Cards,

System Requirements

General	CD ROM drive, 24 bit colour display, 128MB RAM or more recommended
Windows	Pentium II or later with USB or spare PCI slot for FireWire card Windows 98SE/2000/ME/XP (95 & NT via SCSI)
Mac OS 9	Mac with USB or FireWire, Mac OS 8.6 to Mac OS 9.x
Mac OS X	OS X compliant Mac with USB or FireWire, Mac OS X 10.1.5 or 10.2.x Panther supported by SilverFast Ai

Software

Driver	Hazel
Win 98 to XP	ScanWizard, LightLid 35 Calibrator, ABBYY FineReader Sprint, Ulead PhotoExplorer, Adobe Acrobat Reader, Ulead DVD PictureShow, Adobe PhotoDeluxe
Mac OS 8.6 to 9.x	ScanWizard Pro, LanWizard, ICC Profiler, Color Matching System, ABBYY FineReader Sprint, Ulead Photo Explorer, Adobe Acrobat Reader, SilverFast Ai
Mac OS X	SilverFast Ai

Logistics, Warranty

EAN code	4712 8802 01106
Units/pallet	12
Carton dimensions	770 x 500 x 330 mm
Shipping weight	16 kg
Country of origin	Taiwan
Warranty	2 years

Specifications are subject to change without prior notice